

## BIC-2116-N NVR



## Key Features

### Original

- SDA+ over LAN technology inside, One-click Access third-party ONVIF camera
- All channel real-time synchronous playback
- Support IE, Chrome, Firefox, Safari, and browser plug-in free
- All channel synchronous live view and playback by smart phone

### HD Input & Output

- H.265 / H.264 video formats
- Up to 9 8MP IP camera can be accessed
- HDMI at up to 4K, VGA at up to 1080P

### HD Storage & Communication

- 1 HDD supported, Up to 8TB for each
- 1 self-adaptive 10/100M RJ45 interface

### Special

- Instant playback for assigned channel during multi-channel live view mode
- Smart search for selected area in the video, and smart playback to improve the efficiency

## Specifications

<b>Model</b>		BIC-2116-N	
<b>Video / Audio input</b>	<b>IP video input</b>	16 Ch. Up to 8 MP	
	<b>IP audio input</b>	16 Ch.	
	<b>Two-way audio</b>	1x RCA (2.0 Vp-p, 1 kΩ)	
<b>Network</b>	<b>Incoming</b>	<b>Standard</b>	ONVIF, RTSP, HB-protocol
		<b>Bandwidth</b>	80Mbps
	<b>Outgoing</b>	<b>Standard</b>	CGI, RTSP, RTMP(Only for H.264), HB-SDK
		<b>Bandwidth</b>	80Mbps
<b>Video / Audio output</b>	<b>Recording resolution</b>	Up to 8 MP	
	<b>HDMI output</b>	4K (3840 x 2160)/60Hz, 1080p (1920 x 1080)/60Hz, 720p (1280 x 720)/60Hz, UXGA (1600 x 1200)/60Hz, 1280 x 1024/60Hz	
	<b>VGA output</b>	1080p (1920 x 1080)/60Hz, 720p (1280 x 720)/60Hz, UXGA (1600 x 1200)/60Hz, 1280 x 1024/60Hz	
	<b>Audio output</b>	1x RCA (Linear, 1 kΩ)	
<b>Decoding</b>	<b>Decoding standard</b>	H.265 / H.264	
	<b>Live view / playback resolution</b>	Up to 8 MP	
	<b>Synchronous playback</b>	All Ch. Synchronous playback	
<b>HDD</b>	<b>SATA</b>	1 SATA interface for 1 HDD	
	<b>Capacity</b>	Up to 8TB capacity for each HDD	
<b>External interface</b>	<b>Network</b>	1 10/100Mbps self-adaptive RJ45 interface	
	<b>USB</b>	Rear panel: 1x USB3.0 / 1x USB2.0	
	<b>Alarm</b>	2 in / 1 out	
	<b>RS-485</b>	N/A	
<b>General</b>	<b>Power supply</b>	12V 24W	
	<b>Operating condition</b>	-Temperature: -10°C – 55°C (-14°F – 131°F) Humidity: 10 - 90%	
	<b>Dimensions (WxDxH)</b>	254 x 180 x 49.5mm (10" x 7" x 1.9")	